

Product Code - WBXDC-MALE

Male DC Jack Plug Adapter

DC Jack plugs in both male and female versions. Using these units prevents cutting leads on power supplies & cameras



DC JACK MALE 10 pk
12V DC Male
5.5 x 2.1 Male Plug
Warranty Limited Lifetime

WBXDC-FEMALE

Female DC Jack Plug Adapter

DC Jack plugs in both male and female versions. Using these units prevents cutting leads on power supplies & cameras



DC JACK FEMALE 10 pk
12V DC Female
5.5 x 2.1 Female Plug
Warranty Limited Lifetime

HAY-DC JACK PLUG MALE

Male DC Jack Plug Adapter

DC Jack plugs in both male and female versions. Using these units prevents cutting leads on PSUs & cameras



HAY-DC JACK PLUG FEMALE

Female DC Jack Plug Adapter

DC Jack plugs in both male and female versions. Using these units prevents cutting leads on PSUs & cameras



HAY-RJ45-TERM

RJ45 to Terminal connector

RJ45 to screw terminal adapter. Can be used for any RJ45 Application. It is wired in accordance with EIA/TIA 568B wiring standard for structured cabling



HAY-BNC100

1m BNC to BNC Patch cords with RG174 and sleeved BNCs

This useful 60cm BNC patch lead allows fast, economical & safe connection from the VB hub units to your DVR without unnecessary making up of short leads



HAY-2LEDMOD

Dual Flash Led Unit for Bell Boxes battery not included, 1 x CR123A lithium battery 3V required (white light so will flash through blue, red, yellow, green, white and black strobes)



HAY-WSA4 & HAY-WSA3 & HAY-WSA5 & HAY-WSA5-STICKER

CCTV Warning Signs

Data compliant CCTV Warning Sign

A4 - W210mm x L297mm

A3 - W297mm x L420mm

A5 - W154mm x L210mm

A5 - W154mm x L210mm Window Sticker



HAY-BRKT

Dual length camera mounting bracket Internal dual length camera bracket 100mm to 160mm. All metal construction.

Wall or ceiling mount**(subject to top mount on camera body)**

