



The modem card is used to communicate either via Contact ID, Fast Format, SIA or SMS. It will also enable remote uploading/downloading via a PC to the control panel.

Connections:

A = Telephone line output for connection to analogue PSTN telephone line

B = Telephone line output for connection to analogue PSTN telephone line

A-1 = Telephone line output for connection to other telecom equipment

B-1 = Telephone line output for connection to other telecom equipment

NOTE: The ground terminal (TE) should ALWAYS be connected to earth in order to increase the effectiveness of the transient voltage protection on the unit.

Technical Specification:

Formats: Fast Format, Contact ID, SMS , Supports upload/downloading

Baud Rate: 1200bps

Voltage: 12V.d.c.

Quiescent: 20mA (In use: 40mA)

Dimensions: 110 x 56 x 10mm

Declaration of operation mode: Pass-through

Compliance:

Environmental Class II

ATS level: SP2

EN 61000-6-3:2007 + A1: 2011

EN 50130-4: 2011

EN 60950-1:2006 + A12: 2011

ETSI ES 203 021-1 V2.1.1/-2 V2.1.2/-3 V2.1.2

EN 50136-1: 2012

EN 50136-2: 2013



For electrical products sold within the European Community. At the end of the electrical products useful life, it should not be disposed of with household waste. Please recycle where facilities exist. Check with your Local Authority or retailer for recycling advice in your country. Please see the Enforcer 32-WE user, programming and quick set up manuals for further information.

The warranty for this product is 2 years, please visit www.pyronix.com/warranty for more information.