


This product is suitable for use in systems installed to conform to PD6662:2011 at Security Grade 3 Environmental class II and is compliant to EN50131-1

JB701/(WH or BR)

Junction box

5 way screw terminals
2 lid tamper terminals



INSTRUCTIONS

Not suitable for mains voltage operation.

Cable entry can be from either end via snap-out sections, or directly into the unit from behind. The two terminals shown in the illustration should be used for the tamper.

All other terminals are electrically isolated.

Mount on a suitable surface away from damp.

This product is suitable for use in security systems installed to conform to PD6662:2011 at Security Grade 3 Environmental class II (indoor use) and is compliant to EN50131-1

SPECIFICATIONS

| | |
|----------------------------|---|
| Casing material: | ABS |
| Terminals: | 5 x connectors, 2 x tamper |
| Terminal Material: | PBT UL94V0; Pin Header Brass, Tin Plated. |
| Terminal screw: | 2.5mm, steel, Zinc Plated |
| Wire guard: | Stainless Steel |
| Wire Range: | 22-14 AWG, 1.5 mm ² |
| Rated Volts/Rated Current: | 300V/15A |

Environmental Advice.

This product is covered by current WEEE regulations. Please consider the effect on the environment, when disposing of it. Do not put in a domestic waste bin. Only dispose of at an appointed recycling centre.

RoHS Compliant



CQR Security. 125, Pasture Road, Moreton, Wirral. CH46 4TH, United Kingdom

Tel: +44 (0) 151 606 9595 Support: +44 (0) 151 606 6311 email: info@cqr.co.uk Web: <http://www.cqr.co.uk>