

AXIS TA4701 Access Card

Secure access card made from recycled material

Contactless MIFARE[®] DESFire[®] EV2 2K smart card that uses advanced radio frequency identification (RFID) technology to deliver secure and reliable physical access to premises. The card is made of 100% recycled PET-G. One bulk pack comes with 100 cards.

- > **MIFARE[®] DESFire[®] EV2**
- > **100% recycled PET-G**
- > **IP68-rated**
- > **Standard-sized ISO card**



AXIS TA4701 Access Card

General	
Material	PET-G Color: white Recommended minimum printing temperature: 190 °C (374 °F)
Sustainability	PVC free, 100% recycled plastics
Quantity	100 pcs
Dimensions	ISO 7810 85.6 x 54 x 0.8 mm (3.37 x 2.13 x 0.03 in)
Weight	496 g (17.5 oz)
Memory	2 kB Encoding: 500 000 cycles Retention time: 25 years
Electronics	RFID frequency: 13.56 MHz (HF) Chip type: NXP Mifare® DESFire® EV2
Operating conditions	-25 °C to 70 °C (-13 °F to 158 °F)
Storage conditions	-25 °C to 50 °C (-13 °F to 122 °F) Humidity 20-90% RH
Approvals	Environment IEC/EN 60529 IP68 RFID ISO 14443 Other ISO 7810, ISO 10373
Warranty	5-year warranty, see axis.com/warranty

Environmental responsibility:

[axis.com/environmental-responsibility](https://www.axis.com/environmental-responsibility)