



SYSTEMY LINIOWE A/B

DEL 165 A/B jest zaopatrzone w dwie niezależnie pracujące linie nagłośnienia transformatory / głośniki co pozwala na zasilanie z dwóch osobnych przewodów. Dzięki modułom głośników serii A/B zarówno linia A jak i B działają w niezależnych punktach montażowych. W przypadku awarii jednej z linii druga może pracować dzięki czemu utrzymany jest poziom bezpieczeństwa.

Dzięki zastosowaniu bardzo prostego systemu uchwytów opartego na trzech sprężynach głośniki te charakteryzują się szybkim i bardzo łatwym montażem.

A/B LINE-SYSTEMS

The DEL 165 - A/B is equipped with two independent transformer / loudspeaker- combinations and allows loudspeaker's supply by two different wires. By the traditional alternating division of the loudspeakers in the A- and B-line, the breakdown of one line causes an unsupplied area between the next active loudspeaker of the redundancy. Using the loudspeakers of the A/B series the A- as well as the B- line is existing in every mounting position. Accordingly the level loss in the considering area is lighter. If one line fails there will be a higher comprehensibility of speech and security compared to an alternating configuration. The classic appearance and the brilliant acoustic features make this ceiling speaker suitable for diverse acoustic irradiations. The exceptional spring mounting with cropped leg springs guarantees an outstanding rapid ceiling installation.

Dane techniczne / Specifications	
oznaczenie / type	DEL 165/6 - A/B
moc nominalna / Loading rate:	6Watt
Typ głośnika / Chassis-type:	2x77 mm szerokopasmowy / 2x77 mm full range
Zakres częstotliwości / Frequency range (-10dB):	425 - 17 000 Hz
SPL 1W / 1m:	93,1 dB
SPL Pmax / 1m:	100,9 dB
Kąt emisji / Radiation angle 1.000 Hz (-10dB):	180°
Typ transformatora / Transformer:	100 V, 6/3/1,5 Watt
Wymiary / Dimensions:	Ø220 x 100 mm / Installation depth
Otwór montażowy / Cut out	Ø197mm - Ø207mm
Waga / Weight:	1,7 kg
Materiał / Material:	Stal malowana proszkowo / powder-coated, steel panel
Złącze / Connection:	2x2-stykowe łącze samozaciskowe / 2-pole compression clamp
Kolor / Colour:	RAL-9010 Biały / RAL-9010 White
VPE / Packing unit:	12

